



# Specification Data Sheet SDS

## RM RACING ULTRA POWER FLEET MP GREASE 2

Fleet Multi-Purpose Grease was designed for use in a broad range of automotive, agricultural, industrial and general-purpose lubricant applications. It is formulated with select base oil, lithium 12-hydroxystearate thickener, extreme pressure (EP) additives, anti-wear agents and rust, corrosion and oxidation inhibitors to deliver consistent bearing protection over a wide-range of operating conditions.

### Performance Benefits

- Excellent EP and anti-wear performance for a broad-range of service applications
- Outstanding low-temperature performance and grease fluidity
- Maintains grease consistency and lubricating film strength under moderate load
- Excellent protection from water washout

### PRODUCT APPLICATION

Fleet Multi-Purpose Grease is recommended for a wide-range of lubricant applications, including: Automotive drum brake wheel bearings, Plain, rolling-element, antifriction & needle bearings, Automotive chassis and ball & universal joint lubrication, General-purpose agricultural equipment Multi-purpose industrial lubrication 5<sup>th</sup>, and much more

### Typical Characteristics

Test	Method	Unit	Average results
NLGI Consistency			2
NLGI Certification			LB
Thickener Soap, Type			Lithium 12-Hydroxy Stearate
Color			Green
Texture			Smooth
Dropping Point, °F	ASTM D2265	°F	395
Worked Penetration, 60 strokes	ASTM D217		280
Base Oil Viscosity, cSt @ 40°C	ASTM D445	°C	180
Rust Prevention	ASTM D1743		Pass
Oxidation Stability, lb. loss/100 Hrs.	ASTM D942		3
Timken OK Load, lbs.	ASTM D2509	lbs	45
Four-Ball Weld Point	ASTM D2596	kfg	315
Four-Ball Load Wear Index,	ASTM D2596	kfg	40

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

