



# Specification Data Sheet SDS

## RM ALL SEASON HYDRAULIC OIL AW68

All Season AW Oils are high performing hydraulic fluids formulated with highly refined base stocks and an advanced additive system to deliver optimum equipment protection. All Season AW Oils are formulated with anti-wear, anti-oxidation, anti-foam, and anti-rust additive technology to maximize protection and operation life of equipment. high viscosity index delivers peak fluid performance over a widerange of operating temperatures and conditions.

### Performance Benefits

- Protects older hydraulic equipment
- Robust anti wear additives protect critical system components
- Trusted performance over a wide range of operating temperatures and conditions
- Ultimate resistance to rust and oxidation

### PRODUCT APPLICATION

Recommended for use in a variety of farm, off highway construction, logging and industrial equipment. ZXP All Season Hydraulic Oils are suitable for use in aging equipment requiring frequent top off. Recommended for use in ambient temperatures between 0 deg F and 122 deg F (-16 deg C to 50

### Typical Characteristics

Test	Method	Unit	Average results
SAE Grade			68
Viscosity, cSt @ 40°C	ASTM D445	mm <sup>2</sup> /s	68
Viscosity, cSt @ 100°C	ASTM D445	mm <sup>2</sup> /s	9.5
Viscosity index	ASTM D2270		120
Specific Gravity @ 60°F	ASTM D1250		0.8691
Flash Point, COC °C (°F)	ASTM D92	°C (°F)	176 (350)
Pour Point, °F	ASTM D97	°F	-25
Color	ASTM D1500		4.5

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

